

Technical data sheet

Trend23 Derby

Carpet



Article number(s):	15 23 33 38 39
	43 49 65 72
	77 92 93 94
	95 97 98 99

Pictograms / Quality seal / Certificates



DoP number: TEPDERB4_5



Technical data sheet

Trend23 Derby

Material / structure

Type of production	Tufted
Texture	5/64" Frisé
Pile material	100% PA 6 IMPREL®
Backing design	Textile backing
Pile weight (g/m²) approx.	1.200
Pile height (mm) approx.	5,6
Total weight (g/m²) approx.	2.027
Total height (mm) approx.	7,7
Number of tufts/m² approx.	278.400
Dimensions (cm) approx.	400 + 500
Repeat (L x W in cm)	Without repeat

Product characteristics

Hard-wearing value	32 normal - commercial
Comfort value	LC 4 - luxurious
Improvement in impact sound glued (dB) approx.	22
Degree of sound absorption (α_w)	0.20
Lightfastness	≥ 5
Can be laid dissipative	No
Thermal resistance (m²xK/W) approx.	0,12
Fire behaviour	C _{fl} -s1, full-surface adhesion
Anti-static	Yes
Suitable for chair castors	Yes, chair castor type H

Tolerances

Deviation in height	Nominal value + 15 %, - 10 %
Deviation in length	Nominal length ± 1.0 %
Deviation in width	Nominal width ± 1.0 %
Deviation in number of tufts	Nominal value + 10 %, - 7.5%
Deviation in pile weight	Mean value + 13 %, - 10 %
Deviation in total weight	Nominal value ± 15 %

Dimensions and tolerance values in accordance with the standards DIN EN 14159 and EN 1307. Dimensional characteristics and permitted dimensional deviations, which have been determined in the factory, have been given in accordance with the standard.