

Technical data sheet

CV Living 22 Lech

Cushioned vinyl flooring



Article number(s):	215 245 250 255 260
	265 270 275 285 290
	295 400 405 410
	415 420 425 430

Pictograms / Quality seal / Certificates



*On water-bearing systems generally up to a surface temperature of 27 °C

DoP number: CVLECH2/3/4

Technical data sheet

CV Living 22 Lech

Material / structure

Residential class	23	
Commercial class	32	
Industrial class	41	
Total thickness (mm) approx.	2,40	
Wear layer (mm) approx.	0,35	
Surface coating	PU	
Weight per unit area (g/m ²) approx.	1.580	
Available widths (cm)	200 + 300 + 400	
Backing design	Foam backing	
Repeat L x W (cm)	100 x 100	Colour: 215, 245, 250, 260, 270, 275, 285.290
	100 x 100	Colour: 400, 405, 410
	133 x 100	Colour: 255, 265, 295
	100 x 150	Colour: 415, 420
	200 x 150	Colour: 425
	200 x 133	Colour: 430

Product characteristics

Reduction of impact sound (dB) approx.	16
Dimensional stability (%)	≤ 0.20
Static indentation behaviour (mm)	< 0.20
Underfloor heating	suitable*
Lightfastness	≥ 6
REACH	The current requirements are met
Chemical resistance	Resistant
Suitable for chair castors	yes
Fire class	C _{fl} -s1
Skidding behaviour	R10/DS
Thermal resistance approx.	0.03 m ² *K/W
Guarantee	15 years (residential)

*On water-bearing systems generally up to a surface temperature of 27 °C

Tolerances

Deviation in roll length	Not under the nominal value
Deviation in roll width	Not under the nominal value
Deviation in thickness	Nominal value ± 0.20 mm
Deviation in thickness of the wear layer	Nominal value ± 0.05 mm
Deviation in overall mass	Nominal value + 13 % / - 10 %

Dimensions and tolerance values in accordance with DIN EN ISO 26986. Dimensional characteristics and permitted dimensional deviations, which have been determined in the factory, have been given in accordance with the standard.