

Technical Data Sheet

Deluxe Parquet Floors

140 Loft Maxi

2-layer parquet strip in maxi format, Natural grading



Article number(s):	ME101 ME102 ME103

Grading description

Sapwood	mainly free from sapwood
Knots	isolated healthy knots up to 10 mm diameter, filled knots up to 4 mm diameter, isolated black pin knots up to 5 mm diameter
Annual ring position	Quarter sawn, half-quarter sawn, vein, distinctive cross-vein and silver figure
Colour differences	uniform to irregular, wood coloured streaks; slight drying discolourations, brilliant 8-10 mm white streaks along the annual rings
Cracks	isolated permitted
Worm holes	1 - 2 filled work holes
Drying and storage damage	not permitted
Filled cracks	end face up to 100 mm

07/2019

E & OE. Subject to change without notice. All previous data sheets are superseded by this issue.

W. & L. Jordan GmbH | Horst-Dieter-Jordan-Straße 7-10 | D-34134 Kassel | info@joka.de | www.joka.de
 INKU Jordan GmbH & Co. KG | IZ-NÖ Süd | Straße 3 | A-2355 Wiener Neudorf | info@inku.at | www.inku.at

JOKA®
 Natürlich schöne Räume



Technical Data Sheet

Deluxe Parquet Floors

140 Loft Maxi

Despite careful quality controls, up to 3 % of the strips in a lot can come from different grades. (EN 13489)

Material / Construction

Construction	Surface layer: 4.0 mm fine wood +/- 0.2 mm
	Substrate: 5.5 mm HDF substrate
Surface appearance	1-strip
Surface treatment	Natural oil (finally oiled ready for use) / Velvet (matt varnished ready for use)
Connection system	Tongue & groove
Laying options	full adhesive bonding, only right-handed strips in the pack

Dimensions and tolerances in accordance with EN 13489. Dimensional characteristics and permitted dimensional deviations, which have been determined in the factory, have been given in accordance with the type of elements for multi-layered floors.

Dimensions of the individual element

Dimension	Tolerances
Thickness: 9.5 mm	
Length: 1000.00mm	
Width: 90.00mm	
Permitted deviation of the width	+/- 0.2 mm
Permitted deviation of the squareness	≤ 0.1 % across the width
Permitted length deviation	± 0.1 %
Lengthwise curvature across the element	≤ 0.1 % along the length
Cup	≤ 0.3 % across the face
Vertical offset (lipping)	≤ 0.2 mm between the elements

Product characteristic

Moisture content	5 - 9 % at the time of first delivery to EN 13489
Reaction to fire	C _{fl} s1
Formaldehyde emission	E1
Thermal resistance	approx. 0.053 m²*K/W suitability on hot water underfloor heating

Technical Data Sheet

Deluxe Parquet Floors

140 Loft Maxi

Packaging

Contents (area) per pack	2.34 m ²
Contents per pallet	74.88 m ²
Number of elements per pack	26
Packs per pallet	32

General product data

Declaration of performance	AUSPAR5888
----------------------------	------------

NOTE

Wood is a natural product and its colour and texture can therefore differ. Samples, brochures and photos are therefore only approximate and are not binding. The action of sunlight also influences the natural change in wood colour. As a result, the product at the time of delivery can have clear differences to the sample provided.

