### Deluxe Parquet Floors **535 Calgary LD**

### Wide rustic board 1-strip, Elegance grading



Article number(s):	E0101   E0102
	E0103   E0303

Grading description	
Sapwood	not permitted
Silver figure / rays	permitted
Vein / vertical growth rings	permitted
Colour differences	isolated differences permitted due to the natural growth
Intergrown knots	Isolated in the colour of the wood up to 30 mm in diameter
Filled knots	Isolated, up to maximum 15 mm diameter
Cracked knots	Isolated, up to maximum 20 mm diameter (star shake filled in wood colour)
Filled cracks	not permitted
Worm holes	isolated (max. 3 per board)
Surface layer joints	none





### Deluxe Parquet Floors 535 Calgary LD

### Wide rustic board 1-strip, natural grading



Article number(s):	E1003   E1004   E1005   E1006
	E1007   E1008   E1014   E1015
	E1016   E1017   E1018   E1019
	E1113   E 1114   E1313

Grading description		
Sapwood	virtually free from sapwood	
Silver figure / rays	permitted	
Vein / vertical growth rings	permitted	
Colour differences	larger colour differences between the individual top layers and white discolourations	
Intergrown knots	in the colour of the wood up to 50 mm in diameter	
Filled knots	isolated, up to maximum 30 mm diameter	
Cracked knots	isolated, up to maximum 50 mm diameter (star shake filled in wood colour)	
Filled cracks	filled cracks up to 4 mm wide and up to 80 mm long; max. two per board	
Surface layer joints	none	





## Deluxe Parquet Floors 535 Calgary LD

### Wide rustic board 1-strip, Villa grading



Article number(s):	E5003   E5004   E5005   E5010   E5013
	E5020   E5021   E5022   E5023   E5024
	E5026   E5113   E5114   E5313   E5314
	E7043   E7044   E7049

Grading description	
Sapwood	in the longitudinal edges up to max. 3/4 of the board width, in max. approx. 15 % of
Silver figure / rays	permitted
Vein / vertical growth rings	permitted
Colour differences	permitted
Intergrown knots	unlimited if same colour as the wood
Filled knots	up to maximum 50 mm diameter
Cracked knots	isolated, up to maximum 100 mm diameter (star shake filled in wood colour)
Filled cracks	Filled cracks up to 8 mm wide and 300 mm long. max. 2 per board (barrique Villa:
	filled cracks, unlimited in length and frequency, permitted as typical feature)
Worm holes	isolated (max. 3 per board)
Surface layer joints	none





### Deluxe Parquet Floors **535 Calgary LD**

### Wide rustic board 1-strip, Country grading



Article number(s):

Grading description	
Sapwood	permitted
Silver figure / rays	permitted
Vein / vertical growth rings	permitted
Colour differences	permitted
Intergrown knots	unlimited if same colour as the wood
Filled knots	up to maximum 50 mm diameter; splay knots filled black up to 90 x 50 mm
Cracked knots	unlimited (star shake filled black)
Filled cracks	Cracks and ingrown bark max. 25 mm wide, unlimited in length (filled black)
Worm holes	permitted
Surface layer joints	none





## Deluxe Parquet Floors 535 Calgary LD

### Wide rustic board, Fineline grading



Article number(s):	E3303   E3304   N3303

### Grading description

Mixed grading in the factory





# Technical Data Sheet Deluxe Parquet Floors 535 Calgary LD

Despite careful quality controls, up to 3 % of the strips in a lot can come from a different grade. (EN 13489)

Material / Construction	
Construction	Surface layer: 3.5 mm finger +/- 0.2 mm
	Middle layer: 8.8 mm spruce
	Backing: 1.7 mm spruce
Surface design	1-strip board, longitudinal edge chamfered (except Fineline grading)
Surface treatment	Natural oil (finally oiled ready for use) / Velvet (matt varnished ready for use) /
	Velvet Pro (ultra matt varnished ready for use)
Connection system	ProConnect 5G laying system
Laying options	floating installation / full adhesive bonding

Dimensions and tolerances in accordance with EN 13489. Dimensional characteristics and permitted dimensional deviations, which have been determined in the factory, have been given in accordance with the type of elements for multi-layered floors.

Dimensions of the individual element		
Dimension	Tolerances	
Thickness: 14.0 mm		
Length: <b>2,200.0 mm</b>		
Width: 209.0 mm / 181.0 mm / 138.0 mm		
Permitted deviation of the width	+/- 0.2 mm	
Permitted deviation of the squareness	≤ 0.2 % across the width	
Permitted deviation of the length	Not applicable	
Lengthwise curvature across the element	≤ 0.1 % along the length	
Cup	≤ 0.2 % across the face	
Vertical offset (lipping)	≤ 0.2 mm between the elements	

Product characteristic	
Moisture content	5 - 9 % at the time of first delivery to EN 13489
Reaction to fire	D <sub>fl</sub> s1
Formaldehyde emission	≤ 0.05 ppm (E1)
Thermal resistance	approx. 0.093 m <sup>2</sup> x K/W suitability on hot water underfloor heating
Pentachlorophenol content	Below the detection limit





# Technical Data Sheet Deluxe Parquet Floors 535 Calgary LD

Packaging	
Contents (area) per pack	$2.76 \text{ m}^2 / 3.19 \text{ m}^2 / 3.04 \text{ m}^2$
Contents per pallet	138.0 m <sup>2</sup> / 127.6 m <sup>2</sup> / 127.68 m <sup>2</sup>
Number of elements per pack	6/8/8
Packs per pallet	50 / 40 / 42

General product data	
National technical approval	Z-156.607-834
Declaration of performance	PAR1501401

#### NOTE

Wood is a natural product and its colour and texture can therefore differ. Samples, brochures and photos are therefore only approximate and are not binding. The action of sunlight also influences the natural change in wood colour. As a result, the product at the time of delivery can have clear differences to the sample provided.

#### Certificates

















