

Technical Data Sheet

Deluxe Laminate Floors

932 LD Eastside

Laminate 1-strip long board



Article number(s):	9137 9140 9143
	9147 9154 9159
	9175 9188

Material / Construction

Construction of an element	Surface layer: resistant overlay
	Middle layer: HDF coreboard
	Backing: moisture-inhibiting stabilising film
Surface appearance	Long board, V4 chamfered
Surface treatment	Antique texture, synchronous pores
Connection system	ProConnect PURE laying system
Laying options	Floating installation

Technical Data Sheet

Deluxe Laminate Floors

932 LD Eastside

Dimensions and tolerances in accordance with EN 13329. Dimensional characteristics and permitted dimensional deviations, which have been determined in the factory, have been given in accordance with the standard for laminate floorings.

Dimensions of an individual element

Dimension	Tolerances
Thickness: 10 mm	
Length: 2,000.0 mm	
Width: 192.0 mm	
Permitted width deviation of the surface layer	≤ 0.10 mm, relative to nominal value
Permitted deviation of the squareness	≤ 0.20 mm
Permitted length deviation of the surface layer	≤ 0.30 mm/m, relative to the nominal value
Permitted deviation of the element thickness	≤ 0.50 mm, relative to the nominal value
Height difference between joined elements	≤ 0.15 mm
Joint opening between joined elements	≤ 0.20 mm
Straightness of the surface layer	≤ 0.30 mm/m
Flatness of the element	concave width: ≤ 0.15 % convex width: ≤ 0.20 % concave length: ≤ 0.50 % convex length: 1.00 %

Product characteristic

Use class	32
Reaction to fire	C _{fl} s1
Abrasion resistance	AC4
Impact resistance	small diameter ball ≥ 12 N / large diameter ball ≥ 750 mm
Resistance to staining	Group 1 & 2: Grade 5 / Group 3: Grade ≥ 4
Resistance to cigarette burns	Grade 4
Effect of a furniture leg	No damage shall be visible, when tested with foot type 0
Effect of a castor chair	suitable (chair castor type W)
Lightfastness	Blue wool scale ≥ 6 / Greyscale ≥ 4
Slip resistance	DS
Formaldehyde emission	E1
Thickness swelling	≤ 18.0 %
Thermal resistance	0.091 (m ² x K) / W suitable for hot water underfloor heating
Micro-scratch resistance	\leq MSR-B2
Surface soundness	≥ 1.25 N/mm ²

Technical Data Sheet

Deluxe Laminate Floors

932 LD Eastside

Packaging

Contents (area) per pack	1.92 m ²
Contents per pallet	76.80 m ²
Number of elements per pack	5
Packs per pallet	40

General product data

National technical approval	Z-156.606-454
Declaration of performance	PAR1701401

Certificates

