

# Technical Data Sheet

## Deluxe Parquet Floors

### 535 Kingston SB

Ship deck 3-strip, Elegance grading



Article number(s):

E0801 | K0801 | N0801

#### Grading description

Sapwood	not permitted
Knots	isolated healthy knots up to 5 mm
Black knots	isolated black pin knots up to 1 mm diameter
Annual ring position	Quarter sawn, half-quarter sawn, vein up to max. 1/3 of the board width, silver
Colour differences	natural slight colour differences, wood coloured streaks
Cracks	not permitted
Worm holes	not permitted
Drying & storage damage	not permitted
Filled cracks	not permitted

# Technical Data Sheet

## Deluxe Parquet Floors

### 535 Kingston SB

Ship deck 3-strip, Natural grading



Article number(s):	A1800   C1800
	E1800   E1802
	E1803   E1813
	E1864

#### Grading description

Sapwood	not permitted
Knots	isolated healthy knots up to 10 mm, filled knots up 4 mm diameter
Black knots	isolated black pin knots up to 3 mm diameter
Annual ring position	Quarter sawn, half-quarter sawn, vein, distinctive cross-vein and silver figure
Colour differences	uniform to irregular, wood coloured streaks; slight drying discolourations, brilliant 8-10 mm wide white streaks along the annual rings
Cracks	not permitted
Worm holes	1-2 filled work holes per finger
Drying & storage damage	not permitted
Filled cracks	end face up to 100 mm

07/2019

E & OE. Subject to change without notice. All previous data sheets are superseded by this issue.

W. & L. Jordan GmbH | Horst-Dieter-Jordan-Straße 7-10 | D-34134 Kassel | [info@joka.de](mailto:info@joka.de) | [www.joka.de](http://www.joka.de)  
 INKU Jordan GmbH & Co. KG | IZ-NÖ Süd | Straße 3 | A-2355 Wiener Neudorf | [info@inku.at](mailto:info@inku.at) | [www.inku.at](http://www.inku.at)

**JOKA®**  
 Natürlich schöne Räume

**INKU**



# Technical Data Sheet

## Deluxe Parquet Floors

### 535 Kingston SB

Ship deck 3-strip, Villa grading



Article number(s):	E5800   C5800
	E5814   E5874
	E5879

#### Grading description

Sapwood	healthy sapwood with size equal to max. 1/2 the finger width and max. 25 %
Knots	healthy knots up to 12 mm, filled knots up to 12 mm diameter in max. 25 % of the fingers, filled knots up to 10 mm diameter in max. 25% of the fingers
Cracked knots	cracked knots up to 15 mm diameter (filled) in max. 25 % of the fingers
Annual ring position	Quarter sawn, half-quarter sawn, vein, distinctive cross-vein and silver figure
Colour differences	uniform to very irregular, wood coloured streak; slight drying discolourations, brilliant 8-10 mm wide white streaks along the annual rings
Cracks	not permitted
Worm holes	1-2 filled work holes per finger
Drying & storage damage	isolated brown streaks on the end faces and stick marks
Filled cracks	filled permitted

07 | 2019

E & OE. Subject to change without notice. All previous data sheets are superseded by this issue.

W. & L. Jordan GmbH | Horst-Dieter-Jordan-Straße 7-10 | D-34134 Kassel | info@joka.de | www.joka.de  
INKU Jordan GmbH & Co. KG | IZ-NÖ Süd | Straße 3 | A-2355 Wiener Neudorf | info@inku.at | www.inku.at

**JOKA®**  
Natürlich schöne Räume



# Technical Data Sheet

## Deluxe Parquet Floors

### 535 Kingston SB

Ship deck 3-strip, Country grading



Article number(s):	E7800

Grading description	
Sapwood	healthy sapwood with size equal to max. 1/2 the finger width and max. 80 %
Knots	isolated healthy knots up to 5 mm, filled knots up 4 mm diameter
Black knots	isolated black pin knots up to 3 mm diameter
Annual ring position	Quarter sawn, half-quarter sawn, vein, very distinctive cross-vein and silver figure
Colour differences	very irregular, wood coloured streaks; all types of drying discolourations, brilliant 15-20 mm wide white streaks along the annual rings
Cracks	not permitted
Worm holes	1-2 filled work holes per finger
Drying & storage damage	isolated brown streaks on the end faces and stick marks
Filled cracks	filled permitted

# Technical Data Sheet

## Deluxe Parquet Floors

### 535 Kingston SB

Despite careful quality controls, up to 3 % of the strips in a lot can come from a different grade. (EN 13489)

#### Material / Construction

Construction	Surface layer: 3.5 mm fine wood finger +/- 0.2 mm
	Middle layer: 8.8 mm spruce
	Backing: 1.7 mm spruce
Surface design	3-strip ship deck
Surface treatment	Velvet (matt varnished ready for use) / Velvet Pro (ultra matt varnished ready for use) / Satin (satin finish varnished ready for use) /
Connection system	ProConnect 5G laying system
Laying options	floating installation / full adhesive bonding

Dimensions and tolerances in accordance with EN 13489. Dimensional characteristics and permitted dimensional deviations, which have been determined in the factory, have been given in accordance with the type of elements for multi-layered floors.

#### Dimensions of the individual element

Dimension	Tolerances
Thickness: 14.0 mm	
Length: 2,200.0 mm	
Width: 215.0 mm	
Permitted width deviation	± 0.2 mm
Permitted deviation of the squareness	≤ 0.2 % across the width
Permitted length deviation	Not applicable
Lengthwise curvature across the element	≤ 0.1 % along the length
Cup	≤ 0.2 % across the face
Vertical offset (lipping)	≤ 0.2 mm between the elements

#### Product characteristic

Moisture content	5 - 9 % at the time of first delivery to EN 13489
Reaction to fire	D <sub>fl</sub> s1
Formaldehyde emission	E1
Thermal resistance	approx. 0.093 m <sup>2</sup> x K/W suitability on hot water underfloor heating



# Technical Data Sheet

## Deluxe Parquet Floors

### 535 Kingston SB

#### Packaging

Contents (area) per pack	2.84 m <sup>2</sup>
Contents per pallet	142.00 m <sup>2</sup>
Number of elements per pack	6
Packs per pallet	50

#### General product data

Declaration of performance	PAR1501402
----------------------------	------------

#### NOTE

Wood is a natural product and its colour and texture can therefore differ. Samples, brochures and photos are therefore only approximate and are not binding. The action of sunlight also influences the natural change in wood colour. As a result, the product at the time of delivery can have clear differences to the sample provided.

#### Certificates

