

Technical Data Sheet

Deluxe Natural Wood Floors

500 Ativo X3

Natural wood floor, Elegance grading



Article number(s):	AE063 AE065

Grading description	
Sapwood	Not permitted
Oblique grain	Permitted
Vein	Permitted
Natural colour differences	Permitted
Healthy knots	Isolated permitted
Black knots	Isolated, up to maximum 5 mm diameter
Cracks	Permitted up to 3 mm
Red, dark brown streaks	Isolated permitted

Technical Data Sheet

Deluxe Natural Wood Floors

500 Ativo X3

Natural wood floor, Villa grading



Article number(s):	AE563 AE569

Grading description	
Sapwood	Permitted
Oblique grain	Permitted
Vein	Permitted
Natural colour differences	Permitted
Healthy knots	Permitted up to diameter ≤ 70 mm
Black knots	Permitted up to diameter ≤ 40 mm
Cracks	Isolated permitted
Red, dark brown streaks	Permitted

07 | 2019

E & OE. Subject to change without notice. All previous data sheets are superseded by this issue.

W. & L. Jordan GmbH | Horst-Dieter-Jordan-Straße 7-10 | D-34134 Kassel | info@joka.de | www.joka.de
 INKU Jordan GmbH & Co. KG | IZ-NÖ Süd | Straße 3 | A-2355 Wiener Neudorf | info@inku.at | www.inku.at

JOKA®
 Natürlich schöne Räume



Technical Data Sheet

Deluxe Natural Wood Floors

500 Ativo X3

Natural wood floor, Unika grading



Article number(s):	AE763 AE765
	AE767 AE768

Grading description

Sapwood	Permitted
Oblique grain	Permitted
Vein	Permitted
Natural colour differences	Permitted
Healthy knots	Permitted up to diameter ≤ 70 mm
Black knots	Permitted up to diameter ≤ 40 mm
Cracks	Permitted
Red, dark brown streaks	Permitted

Technical Data Sheet

Deluxe Natural Wood Floors

500 Ativo X3

Material / Construction

Construction	Top layer: fine wood with X-Powder technique
	Middle layer: HDF
	Backing: real wood backing
Surface design	1-strip board
Surface treatment	IntensoPro natural oil (naturally oiled ready for use), brushed, V4 chamfered
Connection system	ProConnect 5G laying system
Laying options	floating installation or full adhesive bonding

Dimensions of the individual element

Dimension	Tolerances
Thickness: 11.0 mm	
Length: 2,200.0 mm	
Width: 283.0 mm	
Permitted deviation of the width	+/- 0.2 mm
Permitted deviation of the squareness	≤ 0.2 % across the width
Permitted deviation of the length	Not applicable
Lengthwise curvature across the element	≤ 0.1 % along the length
Cup	≤ 0.2 % across the face
Vertical offset (lipping)	≤ 0.2 mm between the elements

Product characteristic

Reaction to fire	B _{fl} s1
Chemical resistance	Assessment class 1-C to ÖNORM A 1605-12
Thermal resistance	approx. 0.071 m ² x K/W / suitability on hot water underfloor heating
Slip resistance	R10
Brinell hardness	81 N/m ²
Weight per unit area	10.1 kg/m ²

Technical Data Sheet

Deluxe Natural Wood Floors

500 Ativo X3

Packaging

Contents (area) per pack	2.49 m ²
Contents per pallet	97.11 m ²
Number of elements per pack	4
Packs per pallet	39

General product data

Declaration of performance	PAR2101601
----------------------------	------------

NOTE

Wood is a natural product and its colour and texture can therefore differ. Samples, brochures and photos are therefore only approximate and are not binding. The action of sunlight also influences the natural change in wood colour. As a result, the product at the time of delivery can have clear differences to the sample provided.



