#### Technical data sheet

# CV Wood & Stone 22 Malaga

#### Cushioned vinyl flooring



Article number(s):

226 | 229 | 231 | 232 | 233 237 | 239 | 247 | 248

# Certificates



















\*On water-bearing systems generally up to a surface temperature of 27 °C

DoP number: CVMALAGA4



#### Technical data sheet

# CV Wood & Stone 22 Malaga

Material / structure			
Residential class	23		
Commercial class	32		
Industrial class	41		
Total thickness (mm) approx.	2,80		
Wear layer (mm) approx.	0,35		
Surface coating	PU		
Weight per unit area (g/m²) approx.	1.760		
Available widths (cm)	400		
Backing design	Textile back	Textile backing	
Repeat L x W (cm)	100 x 100	Colour: 226, 229, 231, 232, 233, 237, 239	
		Colour: 247, 248	

Product characteristics		
Reduction of impact sound (dB) approx.	19	
Dimensional stability (%)	≤ 0.20	
Static indentation behaviour (mm)	≤ 0.20	
Underfloor heating	suitable*	
Lightfastness	≥6	
REACH	The current requirements are met	
Chemical resistance	No change in material characteristics following brief effect	
Chemical resistance	exposure to diluted acids, oils and greases.	
Suitable for chair castors	yes (caster type W)	
Fire class	C <sub>fl</sub> -s1	
Skidding behaviour	R10/DS	
Thermal resistance approx.	0.04 m <sup>2</sup> xK/W	
Phthalate-free	yes	
Binding agent content	Type 1	
Guarantee	15 years (residential)	

Tolerances	
Deviation in roll length	Not under the nominal value
Deviation in roll width	Not under the nominal value
Deviation in thickness	Nominal value ± 0.20 mm
Deviation in thickness of the wear layer	Nominal value ± 0.05 mm
Deviation in overall mass	Nominal value + 13 % / - 10 %

Dimensions and tolerance values in accordance with DIN EN ISO 26986. Dimensional characteristics and permitted dimensional deviations, which have been determined in the factory, have been given in accordance with the standard.



Information subject to technical modification and error. All previous data sheets are no longer valid on publication of this edition.